


美制 JIC 外螺纹 74° 外锥/

SAE 外螺纹带 O 形圈轻系列 ISO 11926-3 90° 弯

JIC MALE 74° CONE/SAE O-RING BOSS L-SERIES ISO 11926-3 90° ELBOW

1J09-0G



代号尺寸:

代号 PART NO.	螺 纹 THREAD		O 形圈 F 端 O-RING F 端	尺 寸 DIMENSIONS			
	E	F		A	B	S1	S2
1J09-04-03OGZ	7/16"X20	3/8"X24	O903	24.5	28	11	14
1J09-04OGZ	7/16"X20	7/16"X20	O904	24.5	27.2	11	17
1J09-04-05OGZ	7/16"X20	1/2"X20	O905	26.6	29.9	14	17
1J09-04-06OGZ	7/16"X20	9/16"X18	O906	26.6	31.8	14	19
1J09-05-04OGZ	1/2"X20	7/16"X20	O904	26.6	30	14	17
1J09-05OGZ	1/2"X20	1/2"X20	O905	26.6	29	14	17
1J09-05-06OGZ	1/2"X20	9/16"X18	O906	26.6	31.8	14	19
1J09-06-04OGZ	9/16"X18	7/16"X20	O904	26.9	30	14	17
1J09-06-05OGZ	9/16"X18	1/2"X20	O905	26.9	29.9	14	17
1J09-06OGZ	9/16"X18	9/16"X18	O906	26.9	31.8	14	19
1J09-06-08OGZ	9/16"X18	3/4"X16	O908	30	36.8	19	24
1J09-08-04OGZ	3/4"X16	7/16"X20	O904	32	33	19	17
1J09-08-06OGZ	3/4"X16	9/16"X18	O906	33	33.5	19	19
1J09-08OGZ	3/4"X16	3/4"X16	O908	33	36.8	19	24
1J09-08-10OGZ	3/4"X16	7/8"X14	O910	34.8	44	22	27
1J09-08-12OGZ	3/4"X16	1.1/16"X12	O912	37.9	51	27	32
1J09-10-08OGZ	7/8"X14	3/4"X16	O908	38	40	22	27
1J09-10OGZ	7/8"X14	7/8"X14	O910	37.8	44	22	27

1JO9-10-12OGZ	7/8"X14	1.1/16"X12	O912	41	51	27	32
1JO9-12-08OGZ	1.1/16"X12	3/4"X16	O908	45	44	27	24
1JO9-12-10OGZ	1.1/16"X12	7/8"X14	O910	44.2	47	27	27
1JO9-12OGZ	1.1/16"X12	1.1/16"X12	O912	44.2	51	27	32
1JO9-12-16OGZ	1.1/16"X12	1.5/16"X12	O916	47.8	54.5	33	41
1JO9-14OGZ	1.3/16"X12	1.3/16"X12	O914	47.5	53	30	36
1JO9-14-16OGZ	1.3/16"X12	1.5/16"X12	O916	48.5	54.5	33	41
1JO9-16-12OGZ	1.5/16"X12	1.1/16"X12	O912	48.8	54.5	33	32
1JO9-16-14OGZ	1.5/16"X12	1.3/16"X12	O914	49	56	33	36
1JO9-16OGZ	1.5/16"X12	1.5/16"X12	O916	48.8	54.5	33	41
1JO9-16-20OGZ	1.5/16"X12	1.5/8"X12	O920	53.8	59	41	50
1JO9-20-16OGZ	1.5/8"X12	1.5/16"X12	O916	55.5	59.5	41	41
1JO9-20OGZ	1.5/8"X12	1.5/8"X12	O920	55.3	59	41	50
1JO9-20-24OGZ	1.5/8" X12	1.7/8"X12	O924	59.4	63	48	55
1JO9-24OGZ	1.7/8"X12	1.7/8"X12	O924	62.5	63	48	55
1JO9-32OGZ	2.1/2"x12	2.1/2"x12	O932	80	76	63	70

注: F 螺纹端与 ISO 11926-1 油口匹配使用。 Note: F thread end fit with ISO11926-1 port.